Lift Master

These instructions cover the installation of the black/white & color CCTV Camera Kit in Infinity systems equipped for CCTV.

WIRE DISTANCE SPECIFICATIONS

- Power Wire Distance: Up to 100 Feet
- Video Cable Distance: Up to 1000 Feet (max length based on monitor with .25 volt p-p. composite signal sensitivity)

INSTALLATION NOTES

- The CCTV interface board requires a dedicated power supply.
- The video signal is continuously available at J2 on the CCTV interface board.

INSTALLATION

- 1. Remove power to the unit.
- 2. Open front panel of telephone entry unit.
- 3. Pull power wires from power supply to unit.
- 4. Pull video cable from television or CCTV monitor to unit.
- Remove and discard four mounting plate screws and mounting plate from front panel.
- 6. Remove and retain four female-female standoffs. **NOTE:** Male-female standoffs remain in place.
- 7. Remove lens cap from CCTV lens.
- 8. Mount CCTV board on front panel male-female standoffs with J2 coax connector facing the bottom of unit. Make sure camera lens aligns with window in front panel.

CAUTION: Use care with next step. Male-female standoff studs will break if over-tightened.

- 9. Secure CCTV board to front panel using female-female standoffs (previously removed). Carefully snug with 3/16" nut driver.
- Connect coaxial cable with BNC connector to J2 BNC connector on CCTV board.
- 11. Connect the power wire to terminal block TB1 (see Figure 2):
 - Lift blue terminal block off TB1 terminal pins.
 - · Remove "head" and loosen screws.
 - Insert wire into opening on front and tighten screw until wire is held firmly.
 - When both connections are made, plug terminal block back onto pins.

TEST AND ADJUSTMENT

- 1. Plug in AC power supply.
- 2. Turn ON power to unit.
- 3. Plug coax cable into CCTV monitor or television.
- Turn ON CCTV monitor or television. The CCTV picture will appear.
- 5. Close front panel.

CCTV CAMERA KIT

PARTS PROVIDED

Part Number	Qty.	Description
SN1600009 SN1600008	1	Camera Assy. (Color) OR Camera Assy. (Black & White)
SN5300059	1	12V 20VA Transformer
SN5600036	1	Right-Angle BNC Connector
SN6001576	1	Installation Instructions

PARTS NOT PROVIDED

- AC/DC Power Wire: 18 AWG, 2 conductor cable
- Video Wire: Single conductor 75 ohm RG-59U coaxial cable (Belden #9240 or equiv.) with BNC connectors (Amphenol #31-71008 or equiv.)
- CCTV Monitor (or television with video input).



